



## Cisco 350-018 认证题库

认证考试名称: CCIE Pre-Qualification Test for Security

考题数量: 199 Q&As

**Pdf Demo**

### Cisco 350-018 认证考试题库

CCIE 350-018题库由资深IT认证讲师和CCIE 产品专家结合PROMETRIC或VUE的真实考试环境最新原题倾心打造.

题库覆盖了当前最新的真实考题, 并且全部附有正确答案, 我们承诺题库对 CCIE 350-018考试原题完整覆盖.350-018 题库助您轻松通过认证考试, 一次不过全额退款.

**350-018 部分测试题目, 本样题没有包括考题中使用到的图片**

Exam : Cisco 350-018

Title : CCIE Security Qualification Exam

1. Refer to the exhibit. Switch SW2 has just been added to Fa0/23 on SW1. After a few seconds, interface Fa0/23 on SW1 is placed in the error-disabled state. SW2 is removed from port 0/23 and inserted into SW1 port Fa0/22 with the same result. What is the most likely cause of this problem?

- A. The spanning-tree PortFast feature has been configured on SW1.
- B. BPDU filtering has been enabled either globally or on the interfaces of SW1.
- C. The BPDU guard feature has been enabled on the Fast Ethernet interfaces of SW1.
- D. The Fast Ethernet interfaces of SW1 are unable to autonegotiate speed and duplex with SW2.
- E. PAgP is unable to correctly negotiate VLAN trunk characteristics on the link between SW1 and SW2.

Answer: C

2. How do TCP SYN attacks take advantage of TCP to prevent new connections from being established to a host under attack?

- A. sending multiple FIN segments, forcing TCP connection release
- B. filling up a host listen queue by failing to ACK partially opened TCP connections
- C. taking advantage of the host transmit backoff algorithm by sending jam signals to the host
- D. incrementing the ISN of each segment by a random number, causing constant TCP retransmissions
- E. sending TCP RST segments in response to connection SYN+ACK segments, forcing SYN retransmissions

Answer: B

3. Refer to the exhibit. A Cisco security appliance has been correctly configured and inserted between routers R1 and R2. The security

appliance allows IBGP connectivity between R1 and R2 and BGP is fully functional. To increase security, MD5 neighbor authentication is correctly configured on R1 and R2. Unfortunately, BGP stops working after the MD5 configuration is added. Which configuration task must be completed on the security appliance to restore BGP connectivity?

- A. Configure authentication proxy on the security appliance.
- B. Configure the MD5 authentication key on the security appliance.
- C. Add the MD5 key to the security appliance BGP fixup configuration.
- D. Add norandomseq to the static NAT translation on the security appliance.
- E. Configure a GRE tunnel to allow authenticated BGP connections to traverse the security appliance.

Answer: D

4. Refer to the exhibit. The Cisco IOS Software-based switches are configured with VTP and VLANs as shown. The network administrator wants to quickly add the VLANs defined on SW1 to the configuration of SW2. Therefore, the administrator copies the `vlan.dat` file from the flash memory on SW1 to the flash memory of SW2. After the file is copied to SW2, it is rebooted. What is the VLAN status of SW2 after the reboot?

- A. The VLAN information on SW2 will remain the same because it has been configured for transparent VTP mode.
- B. SW2 will clear the `vlan.dat` file and load its VLAN information from the configuration file stored in NVRAM.
- C. A VTP mode mismatch will occur, causing the VLANs in the startup configuration to be ignored and all VLANs above 1005 to be erased.
- D. The VLANs in the `vlan.dat` file will be copied to the running configuration and merged with the extended VLANs defined in the startup configuration.
- E. All VLANs will be erased and all ports will be moved into the default VLAN 1.

Answer: C

5. In regards to private address space, which three of the following statements are true? (Choose three.)

- A. Private address space is defined in RFC 1918.
- B. These IP addresses are considered private:  
10.0.0.0  
172.15.0.0  
192.168.0.0
- C. Private address space is not supposed to be routed over the Internet.
- D. 127.0.0.1 is also considered part of private address space, according to the RFC.
- E. Using only private address space and NAT to the Internet is not considered as secure as having a stateful firewall.

Answer: ACE

6. If an administrator is unable to connect to a Cisco ASA or PIX security appliance via Cisco ASDM, which four of the following items should be checked? (Choose four.)

- A. The HTTPS server is enabled.
- B. The HTTP server is enabled.
- C. The user IP address is permitted in the interface ACL.
- D. The user IP address is permitted in the HTTP statement.
- E. The ASDM file resides in flash memory.
- F. The `asdm` image command exists in the configuration.

Answer: BDEF

7. When using Cisco SDM to manage a Cisco IOS device, what configuration statements are necessary to be able to use Cisco SDM?

- A. `ip http server`
- B. `ip http secure-server`
- C. `ip http server`  
`sdm location X.X.X.X`
- D. `ip http secure-server`  
`sdm location X.X.X.X`
- E. `ip http server`  
`ip http secure-server`

Answer: A

8. Which two of the following statements are attributed to stateless filtering? (Choose two.)

- A. The first TCP packet in a flow must be a SYN packet.
- B. It must process every packet against the inbound ACL filter.
- C. It can look at sequence numbers to validate packets in flow.
- D. It must implement an idle timeout.
- E. It can be used in asymmetrical traffic flows.

Answer: BE

9. Refer to the shown network diagram and configuration. You are hosting a web server at 10.1.1.90, which is under a denial of service attack. Use NBAR to limit web traffic to that server at 200 kb/s. Which of the following configurations is correct to complete the NBAR configuration?

- A.
- B.
- C.
- D.
- E.

Answer: D

10. Which two of the following statements describe why TACACS+ is more desirable from a security standpoint than RADIUS? (Choose two.)

- A. It uses UDP as its transport.
- B. It uses TCP as its transport.
- C. It encrypts the password field with a unique key between server and requester.
- D. Encrypting the whole data payload is optional.
- E. Authentication and authorization are combined into a single query for robustness.

Answer: BD

11. Which three of the following are attributes of the RADIUS protocol? (Choose three.)

- A. encrypts the password
- B. hashes the password
- C. uses UDP as the transport
- D. uses TCP as the transport
- E. combines authentication and authorization in a single request
- F. commonly used to implement command authorization

Answer: BCE

12. Refer to the exhibit. A Cisco security appliance has been inserted between routers R1 and R2 to enhance security and apply advanced protocol inspection. Unfortunately, BGP stopped working after the appliance was inserted in the network. Which three of these configuration tasks must be completed to restore BGP connectivity? (Choose three.)

- A. Configure BGP on the security appliance as an iBGP peer to R1 and R2 in AS 65500.
- B. Configure a static NAT translation to allow inbound TCP connections from R2 to R1.
- C. Configure an ACL on the security appliance allowing TCP port 179 between R1 and R2.
- D. Configure a static route on R1 and R2 using the appliance inside and outside interfaces as gateways.
- E. Configure the BGP fixup feature on the security appliance to permit BGP TCP connections between R1 and R2.

Answer: BCD

13. When designing the addressing scheme of the internal routers at a company, many security professionals choose to use RFC 1918 addresses. Which three of the following addresses are RFC 1918 addresses? (Choose three.)

- A. 0.0.0.0/8
- B. 10.0.0.0/8
- C. 172.16.0.0/12
- D. 172.16.0.0/16
- E. 192.168.0.0/16
- F. 192.168.0.0/24

Answer: BCE

14. What are two key characteristics of VTP? (Choose two.)

- A. VTP messages are sent out all switch-switch connections.
- B. VTP Layer 2 messages are communicated to neighbors using CDP.
- C. VTP manages addition, deletion, and renaming of VLANs 1 to 4094.
- D. VTP pruning restricts flooded traffic, increasing available bandwidth.
- E. VTPv2 can only be used in a domain consisting of VTPv2-capable switches.
- F. VTPv2 performs consistency checks on all sources of VLAN information.

Answer: DE

15. What are two important guidelines to follow when implementing VTP? (Choose two.)

- A. CDP must be enabled on all switches in the VTP management domain.

- B. All switches in the VTP domain must run the same version of VTP.
- C. When using secure-mode VTP, configure management domain passwords only on VTP servers.
- D. Enabling VTP pruning on a server will enable the feature for the entire management domain.
- E. Use of the VTP multidomain feature should be restricted to migration and temporary implementation.

Answer: BD

16. When initiating a new SSL/TLS session, the client receives the server SSL certificate and validates it. What does the client use the certificate for after validating it?

- A. The client and server use the key in the certificate to encrypt all data in the following SSL session.
- B. The server creates a separate session key and sends it to the client. The client has to decrypt the session key using the server public key from the certificate.
- C. The client creates a separate session key and encrypts it with the server public key from the certificate before sending it to the server.
- D. Nothing, the client and server switch to symmetric encryption using IKE to exchange keys.
- E. The client generates a random string, encrypts it with the server public key from the certificate, and sends it to the server. Both the client and server derive the session key from the random data sent by the client.

Answer: E

17. Which two of the following commands are required to implement a Cisco Catalyst 6500 Series FWSM? (Choose two.)

- A. firewall multiple-vlan-interfaces
- B. firewall module x vlan-group y
- C. module x secure-traffic
- D. firewall vlan-group
- E. firewall module x secure-traffic

Answer: BD

18. Which three of these statements describe how DNSSEC prevents DNS cache poisoning attacks from succeeding? (Choose three.)

- A. DNSSEC encrypts all records with domain-specific keys.
- B. DNSSEC eliminates caching and forces all answers to be authoritative.
- C. DNSSEC introduces KEY records that hold domain-specific public keys.
- D. DNSSEC deprecates CNAME records and replaces them with DS records.
- E. DNSSEC utilizes DS records to establish a trusted hierarchy of zones.
- F. DNSSEC signs all records with domain-specific keys.

Answer: CEF

19. A firewall administrator received this syslog message from his adaptive security appliance. What can the firewall administrator infer from the message?

- A. The server at 209.165.201.10 is under a smurf attack.
- B. The server at 10.1.1.20 is under a SYN attack.
- C. The client at 209.165.201.10 has been infected with a virus.
- D. The server at 10.1.1.20 is under a smurf attack.

Answer: B

20. According to RFC 3180, what is the correct GLOP address for AS 456?

- A. 224.0.4.86
- B. 224.4.86.0
- C. 233.1.200.0
- D. 239.2.213.0
- E. 239.4.5.6

Answer: C

购买 [350-018 题库](#)

### **QuickPass 提供专业350-018题库**

#### 1. 3个月内免费升级服务

所有购买我们“350-018题库”的客户，都将获得3个月内免费升级的售后服务，确保客户的一次通过率。

#### 2. 高质量和高价值的 350-018 题库

350-018 考题由我们的资深IT认证讲师和 CCIE 产品专家精心打造,包括了当前最新的真实 350-018 考题，全部附有正确答案。

#### 3. 100% 保证您通过 CCIE 考试并且获得 CCIE 证书

所有购买 "350-018 题库" 的客户都将得到3个月的免费升级服务, 保证了客户的一次通过率.QuickPass 助您一次通过CCIE 350-018考试。

购买、使用QuickPass 350-018题库, 我们可确保您一次通过考试。

1. 本题库源自合作考试中心的真实考试原题, 截屏后由我们的专业团队汇总整理, 再经过合作培训中心资深IT认证讲师对考题校对, 保证了认证考试题库的专业品质, 题库试题正确率100%, 对350-018认证考试考题覆盖率96%以上。您只需在参加 350-018 认证前整体学习下本题库, 必定可以轻松完成考试, 一次通过认证。

2. QuickPass实行“一次不过全额退款”承诺。如果您购买了我们的 350-018考题, 只要不是首次通过, 凭盖有PROMETRIC或VUE考试中心钢印的考试成绩单, 我们将退还您购买 350-018 的全部费用, 绝对保证您的利益不受到任何的损失。

3. 我们提供完善的售后服务, 对所有购买题库的客户提供跟踪服务, 在您购买考题后的3个月内, 享受免费升级考题服务, 如果在这期间, 认证考试中心对 350-018 考题做出修改或变题, 我们会在第一时间更新相关题库, 并免费提供给您更新下载。

(350-018) 属于 CCIE 认证考试中的一门, 如果需要取得 CCIE 证书, 您可能还需要参加其他相关考试, 详情可访问 [CCIE 题库](#) 认证专题, 在那里, 你将看到所有 CCIE 认证相关考试科目。

QuickPass专业提供CCIE 350-018最新题库, 完全覆盖350-018考试原题. 使用我们的完善的CCIE 资源, 你将尽量减少CCIE 考试的成本并将你的第一次尝试中通过 350-018认证考试。100%退款保证!

#### 350-018 相关题库

350-001	350-018	350-030	350-001- LAB	350-029 351-001
350-018- LAB	350-040	350-022	350-024	350-050
350-021	350-020	350-027	350-025	351-018
	350-026	350-023	350- 001GB2312- LAB	

#### 其他 Cisco 认证题库

350-023	650-178	646-411	642-832	646-096
642-356	646-574	642-821	650-175	350-025
650-621	642-081	642-062	646-222	642-067
650-393	646-202	642-383	350-018- LAB	642-971